Aster A-680
Network Packet Broker

Technical Data Sheet

Microtel innovation


Product Description

10/25/40/100 Gbps Packet Broker

Aster A-680 Packet Broker provides a **comprehensive Network Packet Brokering for 10/25/40/100 Gbps** links.

Designed with a 2U box, Aster A-680 provides the capability to interface network traffic with a single device, **no matter if 10/25/40/100 Gbps interfaces are used,** and to **aggregate, filter and load balance** towards the monitoring tools at different speeds.

A-680 implements **Advanced Packet Manipulation (APM) functionalities, like Packet Slicing, Header Stripping, Timestamping and Tunnel Encapsulation/ Decapsulation capabilities,** to improve monitoring tools efficiency and send and get data to/from NFV infrastructure.




Key features

- **Input/output ports:**
  - **10/25/40/100 Gbps** visibility in 2U form factor
  - 64 cages are available, each one to be used as 1 100Gbps, 1 40Gbps, 4 25Gbps, 4 10Gbps, as needed
  - All cages are enabled, no need for additional licences
- **Filtering, Aggregation and Load Balancing:**
  - Filtering based on L2-L5 parameters
  - Selective aggregation: Any to Any, Many to One, One to Many
  - Inner/Outer IP addresses, IP protocol and L4 ports Load Balancing
  - Support Jumbo Packets, up to 10240 bytes
- **L2GRE, L3GRE, VXLAN Tunnel Start/Termination**
- **Advanced Packet Manipulation (APM) capabilities:**
  - Packet slicing
  - MPLS, VLAN, VLAN Q-in-Q, VNTag, ERSPAN Header Stripping
  - L2GRE, L3GRE, VXLAN, GTP-U Detunneling
  - VLAN ID replacement
  - VLAN, MPLS Tag adding and removal
  - Source port Labelling (VLAN)
  - Timestamping
- **Extra capabilities:**
  - Up to 5 MPLS Labels parsing and removal
  - Loopback ports for multiple APM actions
  - PCAP snapshot capture
- **Management:**
  - CLI and GUI for local and remote management
  - API RESTful
  - Real time statistics, counters and SNMP alarms
  - Dashboard for statistics and alarms analysis
  - TACACS+, RADIUS

Highlights

- Integrate the Packet Brokers Capture Fabric with your virtual network infrastructure, **using Tunnel Encapsulation/Decapsulation capabilities to get data from NFV and to send data to virtual probes**
- **Improve tool efficiency** through packet slicing and header stripping functionalities
- **Deliver the right data to monitoring tools** by filtering network traffic at Layers 2-4 using **both inner and outer parameters,** as well as UDF-based filtering capabilities by offset matching
- **High density solution with low power consumption:** up to 64 100G ports in 2U space, with maximum power consumption limited to 850W



Aster A-680
Network Packet Broker

Technical Data Sheet

Microtel innovation

Aster A-680 — Technical Specifications

Input/Output Capabilities	
Number of physical ports	64 cages, supporting QSFP28 (1x100Gbps or 4x25Gbps) and QSFP+ (1x40Gbps or 4x10Gbps)
Performances	Switching Capacity: 6.4 Tbps
Management	
Management ports	10/100/1000BASE-T port, RJ45 connector
Protocols	IPv4, IPv6, SNMPv2, SNMPv3, HTTPS, TACACS+, Syslog
Statistics and Alarms	Real time statistics and counters for each input output ports SNMP Traps alarms

Aster A-680 — Ordering Information

A-680-FL-64C/AC	2RU Chassis, 64x40/100G in/out ports, all ports enabled (QSFP+/QSFP28 not included). Advanced Packet Manipulation features included. Redundant AC power supply.
A-680-FL-64C/DC	2RU Chassis, 64x40/100G in/out ports, all ports enabled (QSFP+/QSFP28 not included). Advanced Packet Manipulation features included. Redundant DC power supply.
QSFP+-SR/M-4	QSFP+ SR4 - 40G Parallel Fiber - Multimode (850nm) with MPO/MTP connector.
QSFP+-LR/M-4	QSFP+ LR4 - 40G Parallel Fiber - Single-mode (1310nm) with MPO/MTP connector.
QSFP+-LR/L-4	QSFP+ LR4 - 40G CWDM Single-mode (1310nm) with LC connector.
QSFP28-SR/M-4	QSFP28 for 100G Parallel Fiber - Multimode (850nm) with MPO/MTP connector.
QSFP28-PSM4/M-4	QSFP28 for 100G Parallel Fiber - Single-mode(1310nm) with MPO/MTP connector.
QSFP28-LR4/L	QSFP28 for 100G LAN-WDM Single-mode (1310nm) with LC connector.
CML-14-3-MM-2m	Breakout cable MTP/MPO connector (Female) to LC connectors 4 x 10G (Male), Multimode 850nm, OM3, 50/125 um, 2m lenght . To be used with QSFP+-SR/M-4.
CML-14-4-MM-2m	Breakout cable MTP/MPO connector (Female) to LC connectors 4 x 10G (Male), Multimode 850nm, OM4, 50/125 um, 2m lenght. To be used with QSFP+-SR/M-4.
CML-14-SM-2m	Breakout cable 1 x 40G (MPO/MTP connector) to 4 x 10G (8 x LC connectors), OS1/OS2, Single-mode, (1310 nm) 9/125 um; 2m length. To be used with QSFP+-LR/M-4.

Operating	Power	Dimensions	Regulatory
• Operating temperature: 0°C to 45°C (32°F to 113°F) • Operating Humidity: 10% to 90% non-condensing	• Redundant, load sharing, hot-swappable AC or -48VDC PSUs • Input voltage 90 to 240VAC at 50-60Hz, -36 to -72VDC Typical power consumption: 650W • Max power consumption: 850W without pluggable optics • Field serviceable cooling	• Chassis 2U, 19" rack mount, (WxDxH): 438 mm x 580 mm x 88 mm (17.2 x 22.8 x 3.5 in) • Weight 14.11 kg (31.1 lbs)	• CE, FCC, RoHS6 compliant